



TC-C32QN Spec:I3/E/Y/C/4mm/V5.1

2MP Fixed Bullet Camera

AK Series



KEY FEATURES

- Metal+Plastic Housing
- Up to 1920x1080@30fps
- S+265/H.265/H.264
- Min. illumination Color: 0.04Lux@F2.2
- Smart IR, IR Range: 30m
- Built-in Mic
- Operating Conditions -30°~60°, 0~95% RH
- POE, IP67



Tiandy Technologies Co.,Ltd.


SPECIFICATIONS

Camera	
Image Sensor	1/3"CMOS
Min. Illumination	Color:0.04Lux@(F2.2,AGC ON),B/W:0Lux with IR
Shutter Time	1s to 1/100,000s
Day&Night	IR-cut filter with auto switch (ICR)
WDR	DWDR
S/N	>37dB
Angle Adjustment	0-360°;0-80°;0-360°
Lens	
Lens Type	Fixed
Focal Length	4mm
Lens Mount	M12
Aperture Range	F2.2,Fixed
Field of View	76°(H);41.2°(V);87°(D)
DORI Distance	Detect:57.1m Observe:22.6m Recognize:11.4m Identify:5.7m
Illuminator	
IR LEDs	2
IR Distance	30m
Wavelength	850nm
Compression Standard	
Video Compression	S+265/H.265/H.264B/H.264M/H.264H
Video Bit Rate	32k-4Mbps
Audio Compression	G.711A/G.711U
Audio Sampling Rate	8kHz
Image	
Max. Resolution	1920x1080@30fps
Main Stream	PAL:25fps(1920x1080,1280x720,704x576,640x480) NTSC:30fps(1920×1080,1280×720,704×480,640×480)
Sub Stream	PAL:25fps(704x576,704x288,352x288,640x360) NTSC:30fps(704x480,704x240,352x240,640x360)
BLC	Yes
HLC	Yes
AGC	Yes
3D DNR	Yes



White Balance	Auto/Semi-auto/Manual
OSD	1region;16*16/32*32/48*48
Privacy Mask	4 regions
Defog	Yes
Network	
Protocols	HTTP;TCP/IP;UDP;ICMP;DHCP;DNS;NTP;IPv4;Telnet;Unicast
System Compatibility	onvif Profile S/T
Remote Connection	1
Moblle Client	N/A
Web	IE10+;Firefox52+;Edge89+;Safari11+;Chrome57+
Interface	
Communication Interface	1 RJ45 10M/ 100M self adaptive Ethernet port
Built-In Mic	Yes
General	
Web Client Language	English
Operating Temperature	-30°C-60°C
Operating Humidity	0-95%
Storage Temperature	-30°C-60°C
Storage Humidity	0-95%(non-condensing)
Power Supply	POE 802.3af;MAX 5.5W
Protection	Surge protection 2000V;Lightning proof 6000V;IP67
Boundary Dimensions	164(L)73(W)73(H)mm
Package Dimensions	180(L)90(W)95(H)mm
GrossWeight	0.3kg
NetWeight	0.22kg

DIMENSIONS (Unit: mm)



ACCESSORIES



TC-P54BM Spec:V5



A36

.