

# Tiandy



TC-R324160 Spec: E/B/R/N/V4.0

## H.265 24HDD 160ch Redundant power supply NVR

Ultra Series



### KEY FEATURES

#### HD Input

- S+265/H.265/H.264 video formats
- Connectable to the third-party network cameras
- Support live view, storage, and playback of the connected camera at up to 12MP resolution

#### HD Output

- HDMI and VGA independent outputs
- HDMI Video output at up to 4K resolution

#### HD Storage

- 24 SATA interface, up to 10TB for 1 HDD
- S+265 compression effectively reduces the storage space and costs by up to 75%

#### HD Transmission

- 4×RJ45 self-adaptive 10/100/1000 Mbps network interface

#### Stability assurance

- Hot swap HDD
- Redundant power

#### Various Applications

- Centralized management of IP cameras, including configuration, information import/export, real-time information display, upgrade, etc.
- Connectable to smart IP cameras from Tiandy and the recording, playing back, and backing up of VCA alarms can be realized
- VCA detection alarm is supported
- Web6 supports plug-in free browsing and can preview videos on all browsers
- Support cloud upgrade






Input	
Video Input	160-ch
Max Resolution	12MP
Two-way Audio Input	1-ch, 3.5mm
Bandwidth	Income 800Mbps; Outgoing 400Mbps
Output	
HDMI/VGA Output	HDMI 2-ch, 3840×2160, 1920×1080, 1280×720, 1024×768, 1366×768, 1440×900, 1280×800 VGA 1-ch, 1920×1080, 1280×720, 1024×768, 1366×768, 1440×900, 1280×800
Screen Split	1/2/3/4/5/6/7/8/9/10/12/13/16/20A/20B/25/32/36/40/64/80
Audio Output	1×3.5mm, 1×BNC
Decoding	
Decoding Format	S+265/H.265/H.264
Recording Resolution	12MP/8MP/6MP/5MP/4MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Preview Capability	4×12MP, 6×8MP, 8×6MP, 9×5MP, 12×4MP, 16×3MP, 24×1080P, 48×720P, 80×4CIF
Synchronous Playback	4×12MP, 6×8MP, 8×6MP, 9×5MP, 12×4MP, 16×3MP, 16×1080P, 16×720P
Records Encryption	Yes
Hard Disk	
SATA	24 SATA interface for 24 HDDs
Capacity	Up to 10TB for each HDD
eSATA Interface	1 eSATA interface
Array Type	JBOD, RAID0/1/5/6/10/50/60
External Interface	
Network Interface	4×RJ45 self-adaptive 10/100/1000 Mbps network interface
USB Interface	2×USB 2.0, 1×USB 3.0
Serial Interface	2×RS485, 1×RS232
Alarm In/Out	16/8
Network	
Protocol	HTTP, HTTPS, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP(v1), DHCP, DNS, DDNS, EasyDDNS, NTP, SMTP, SSL, QoS, IPv4, IPv6, IP Filter, PPPOE, Telnet, SSH, RTSP, RTP, RTCP, ARP, NAS(NFS、SMB/CIFS)
System Compatibility	ONVIF (PROFILE S/T/G), SDK, P2P
General	
Web Version	Web6
Language	Simplified Chinese, Traditional Chinese, English, Spanish, Italian, Korean, Turkish, Russian, Thai, French, Hebrew, Polish, Dutch, Arabic, Vietnamese, German, Ukrainian, Portuguese
Operating Conditions	-10 ~ 55°C, 10%~90% RH
Power Supply	AC100~240V, 50/60HZ
Redundant Power	Yes
Consumption (without HDD)	< 50W
Chassis	4U
Dimensions	542×446.6×173.8 mm (21.34×17.58×6.84 inch)
Weight (without HDD)	17.5Kg (38.58lb)


AVAILABLE MODEL

TC-R324160 SPEC: E/B/R/N/V4.0

**DIMENSIONS (Unit: mm)**



## Physical Interfaces



DISTRIBUTED BY



Tiandy Technologies Co.,Ltd.